



## Pulling & Lifting Machine Heavy Duty

### Adjustable handle

for easy operation.

### Backward lever & Forward lever

placed in tandem providing a slim design and assuring power transfer along the center.

### Spare shear pins

Two spare shear pins located in the carrying handle.

### Built-in shearing pin

prevent overload. It functions at approx. 50% overload and the pins can be replaced without removing the load.

### Anchor bolt

offers numerous and versatile connection possibilities with load hooks, sling ropes and sling chains.

### Stamped serial number

for easy identification.

### High strength cast aluminum alloy body

Light weight, simple to operate. Smooth contour design with large flat bottom surface for increased stability in horizontal as well as vertical working position.

### Galv. steel wire rope mounted on a reel

every ropes is operationally tested to 150% of the rated capacity and is issued with an individual test certificate.



### Specifications

Rated Capacity (T)	Pulling Capacity (T)	Rated forward travel (mm)	Rope diameter (mm)	Standard length of rope (m)	Net weight (kg)	Rated forward hand power (N)	Max. Overall size (mm)
0.8	1.2	≥ 52	8	20	15	≥ 331	428 x 64 x 235
1.6	2.4	≥ 55	11	20	27	≥ 445	428 x 64 x 235
3.2	4.8	≥ 28	16	20	46	≥ 441	545 x 97 x 286
5.4	8	≥ 30	20	20	95	≥ 745	660 x 116 x 350